

PUREDATOR®

PREDATORTIRES.COM



Conquer any challenge with the New Mutant X-MT, the most aggressive tire in the New Mutant lineup. The maximum traction mud terrain is designed with a dynamic tread pattern with high void ratio; it evacuates mud, dirt, snow, sand and rocks with ease for constant traction.

For extended service life and durability, the X-MT features deep tread blocks and massive side lugs that bite into loose rock and uneven surfaces. This delivers superior grip, puncture resistance, and provides confidence when navigating on harsh terrain.

On pavement, the X-MT delivers a comfortable ride. Its variable three-pitch tread pattern minimizes noise and vibration. From rock crawling and mud bogs to rolling big lifted trucks or heavy loads, the X-MT is built to take on punishment. Its durable construction ensures reliable performance, mile after mile.





NEW MUTANT X-MT

Maximum Traction Mud Tire



*Ratings are on a scale of 1-10

- High void-to-lug ratio for extreme off-road conditions: This design keeps the tread clear and provides superior traction in mud, snow, sand, and rocky terrain.
- Staggered shoulder lugs: These lugs enhance grip and biting edge on rocky terrain.
- Deep tread depth: This provides better off-road capability, hydroplaning resistance, and a longer tread
- Deep siping in the tread blocks: This improves grip and braking performance in winter and on wet surfaces.
- Mud and stone ejectors: These features help to shed mud and prevent stones from drilling into the tire.
- Advanced "X" tread pattern: This design maximizes traction in any off-road terrain.
- Aggressive "X-TREME SPIKE" X-MT dual sidewall design: This design offers added off-road traction, sidewall armor, and a unique aesthetic.









WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD Inch	SW	TD 32ND	SIDEWALL
	LT265/70R17	10PR 121/118Q	NPRXMT01	8.1	7.0-9.0	31.65	10.71	18.2	BLK
17"	LT285/70R17	10PR 121/118Q	NPRXMT02	8 1/2 J	7.5-9.5	32.76	11.50	18.2	BLK
"	33X12.50R17LT	10PR 120Q	NPRXMT03	10J	8.5-11.0	32.52	12.50	20.2	BLK
	35X12.50R17LT	10PR 121R	NPRXMT04	10J	8.0-10.5	34.52	12.50	20.2	BLK
	LT275/70R18	10PR 125/122R	NPRXMT05	8.J	7.0-9.0	33.19	10.98	18.2	BLK
18"	33X12.50R18LT	10PR 118Q	NPRXMT06	10J	8.5-11.0	32.52	12.50	20.2	BLK
	35X12.50R18 LT	10PR 123R	NPRXMT07	10J	8.5-11.0	34.52	12.50	20.2	BLK
	LT275/55R20	10PR 120/117Q	NPRXMT08	8 1/2 J	8.0-9.5	31.89	11.18	18.2	BLK
	LT285/55R20	10PR 122/119Q	NPRXMT09	9.J	8.5-10.0	32.36	11.69	20.2	BLK
	33X11.50R20LT	10PR 118Q	NPRXMT10	9,1	8.0-10.5	32.52	11.42	20.2	BLK
20"	33X12.50R20LT	10PR 114Q	PRXMT11	10J	8.5-11.0	32.52	12.50	20.2	BLK
20	33X12.50R20LT	12PR 119Q	PRXMT12	10J	8.5-11.0	32.52	12.50	20.2	BLK
	35X12.50R20LT	10PR 121Q	PRXMT13	10J	8.5-11.0	34.52	12.50	20.2	BLK
	35X12.50R20LT	12PR 125Q	PRXMT14	10J	8.5-11.0	34.52	12.50	20.2	BLK
	37X13.50R20 LT	12PR 128Q	NPRXMT15	11J	9.5-12.0	36.52	13.58	20.2	BLK
VAN	33X12.50R22LT	10PR 109R	PRXMT16	10J	10.0-12.0	32.52	12.45	20.2	BLK
	33X12.50R22LT	12PR 114Q	PRXMT17	10J	10.0-12.0	32.52	12.45	20.2	BLK
22"	35X12.50R22LT	10PR 117R	PRXMT18	10J	8.5-11.0	34.52	12.50	20.2	BLK
	35X12.50R22LT	12PR 121Q	PRXMT19	10J	8.5-11.0	34.52	12.50	20.2	BLK
	37X13.50R22 LT	12PR 128Q	NPRXMT20	11J	9.5-12.0	36.52	13.58	20.2	BLK

WHEEL DIAMETER	SIZE	LS	PARTS Number	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW	TD 32ND	SIDEWALL
	33X13.50R24 LT	12PR 113Q	NPRXMT21	12 1/2 J	11.5-12.5	32.52	13.58	20.2	BLK
24"	35X13.50R24LT	12PR 116Q	NPRXMT22	12 J	11.5-13.5	34.52	13.44	20.2	BLK
	37X13.50R24LT	12PR 124Q	NPRXMT23	11,1	9.5-12.0	36.52	13.58	20.2	BLK
26"	37X13.50R26LT	12PR 117Q	NPRXMT24	11,	10.5-13.0	36.52	13.44	20.2	BLK
20"	42X16.50R30LT	10PR 126Q	NPRXMT25	15J	14.5-16.0	41.54	16.57	20.9	BLK
30"	44X16.50R30LT	10PR 128Q	NPRXMT26	15J	14.0-16.0	43.50	16.57	20.9	BLK





^{*}Every effort has been made to verify the accuracy of the listed specifications. Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.






NEW MUTANT X-RT

Rugged-Terrain Tire







*Ratings are on a scale of 1-10

- Optimized Void-to-Lug Ratio: This design enhances off-road traction in mud, snow, sand, and rocky terrain by allowing for better self-cleaning of the tread.
- Deep Tread Depth: Provides increased off-road capability, improved hydroplaning resistance, and extends the tire's lifespan.
- Staggered Shoulder Lugs: These lugs offer a biting edge for superior grip on rocky surfaces.
- Mud and Stone Ejectors: Located between the shoulder lug blocks, these features help shed mud and prevent stones from getting lodged in the tread.
- Advanced "X" Tread Pattern with Pitch Variation: This design reduces road noise for a quieter highway ride, enhancing comfort for drivers and passengers.
- Aggressive "TALON" X-RT Dual Sidewalls: This design not only provides additional off-road traction and sidewall protection but also offers drivers a unique visual customization option.











WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD Inch	SW	TD 32ND	SIDEWALL
	LT265/70R17	10PR 121/118Q	PRXRT42	8,1	7.0-9.0	31.65	10.71	16.5	BLK
	LT285/70R17	10PR 121/118Q	PRXRT43	8 1/2 J	7.5-9.5	32.76	11.50	16.5	BLK
	LT305/65R17	10PR 121/118Q	PRXRT01	9,1	9.0-11.0	32.60	12.24	18.6	BLK
17"	33X12.50R17LT	10PR 120Q	PRXRT05	10J	8.5-11.0	32.52	12.50	18.6	BLK
17	35X12.50R17LT	10PR 121R	PRXRT32	10J	8.0-10.5	34.52	12.50	18.6	BLK
	37X12.50R17 LT	8PR 124Q	PRXRT44	10J	8.0-10.5	36.52	12.50	19.1	BLK
	37X12.50R17 LT	10PR 128Q	PRXRT45	10J	8.0-10.5	36.52	12.50	19.1	BLK
	37X13.50R17 LT	10PR 128Q	PRXRT46	11J	9.0-11.5	36.52	13.58	19.1	BLK
	LT275/70R18	10PR 125/122Q	PRXRT34	81	7.0-9.0	33.19	10.98	16.5	BLK
18"	LT305/60R18	10PR 121/118Q	PRXRT02	9,1	9.0-11.0	32.40	12.24	18.6	BLK
10	33X12.50R18LT	10PR 118Q	PRXRT06	10J	8.5-11.0	32.52	12.50	18.6	BLK
	35X12.50R18LT	10PR 123R	PRXRT33	10J	8.5-11.0	34.52	12.50	18.6	BLK
	LT275/55R20	10PR 120/117Q	PRXRT03	8 1/2 J	8.0-9.5	31.89	11.18	18.6	BLK
	LT275/65R20	10PR 126/123R	PRXRT35	8.1	8.0-9.5	34.09	10.98	16.5	BLK
	LT285/55R20	10PR 122/119Q	PRXRT04	9,1	8.5-10.0	32.36	11.69	18.6	BLK
20"	LT305/55R20	12PR 125/122S	PRXRT36	91/2J	9.0-11.0	33.23	12.44	16.5	BLK
20	33X11.50R20LT	10PR 118Q	PRXRT07	9,1	8.0-10.5	32.52	11.42	18.6	BLK
	33X12.50R20LT	10PR 114Q	PRXRT08	10J	8.5-11.0	32.52	12.50	18.6	BLK
	33X12.50R20LT	12PR 119Q	PRXRT09	10J	8.5-11.0	32.52	12.50	18.6	BLK
	33X13.50R20LT	12PR 120Q	PRXRT12	11,1	9.5-12.0	32.52	13.58	20.4	BLK

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
	35X12.50R20LT	10PR 121Q	PRXRT10	10J	8.5-11.0	34.52	12.50	18.6	BLK
	35X12.50R20LT	12PR 125Q	PRXRT11	10J	8.5-11.0	34.52	12.50	18.6	BLK
	35X13.50R20LT	12PR 126Q	PRXRT13	11J	9.5-12.0	34.52	13.58	20.4	BLK
20"	37X12.50R20 LT	12PR 128Q	PRXRT37	10J	8.5-11.0	36.52	12.50	19.1	BLK
	37X13.50R20 LT	12PR 128Q	PRXRT38	11,1	9.5-12.0	36.52	13.58	19.1	BLK
	38X15.50R20LT	10PR 128Q	PRXRT14	12 1/2 J	11.0-14.0	37.52	15.54	20.4	BLK
	40X15.50R20LT	12PR 128Q	PRXRT15	12 1/2 J	11.0-14.0	39.52	15.54	20.4	BLK
	33X12.50R22LT	10PR 109Q	PRXRT16	10J	10.0-12.0	32.52	12.45	18.6	BLK
	33X12.50R22LT	12PR 114Q	PRXRT17	10J	10.0-12.0	32.52	12.45	18.6	BLK
	33X13.50R22LT	12PR 116Q	PRXRT26	11J	10.5-12.0	32.52	13.58	20.4	BLK
00"	35X12.50R22LT	10PR 117Q	PRXRT18	10J	8.5-11.0	34.52	12.50	18.6	BLK
22"	35X12.50R22LT	12PR 121Q	PRXRT19	10J	8.5-11.0	34.52	12.50	18.6	BLK
	35X13.50R22LT	12PR 122Q	PRXRT27	11,1	10.5-12.0	34.52	13.58	20.4	BLK
	37X13.50R22 LT	12PR 128Q	PRXRT39	11J	9.5-12.0	36.52	13.58	19.1	BLK
	40X15.50R22LT	12PR 128Q	PRXRT20	12 1/2 J	11.0-14.0	39.52	15.54	20.4	BLK
	33X13.50R24LT	10PR 109Q	PRXRT28	12 J	11.5-12.5	32.52	13.58	20.4	BLK
	35X13.50R24LT	12PR 116Q	PRXRT21	12 J	11.5-13.5	34.52	13.44	20.4	BLK
24"	37X13.50R24 LT	12PR 124Q	PRXRT40	11,1	9.5-12.0	36.52	13.58	19.1	BLK
	38X15.50R24LT	12PR 128P	PRXRT29	12 1/2 J	12.5-14.5	37.52	15.43	20.4	BLK
	40X15.50R24LT	12PR 128P	PRXRT22	12 1/2 J	11.0-14.0	39.52	15.54	20.4	BLK

WHEEL NAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD Inch	SW	TD 32ND	SIDEWAL
	35X13.50R26LT	10PR 118Q	PRXRT30	12 1/2 J	11.5-12.5	34.52	13.58	20.4	BLK
	37X13.50R26LT	12PR 117Q	PRXRT41	11J	10.5-13.0	36.52	13.44	19.1	BLK
26"	38X15.50R26LT	12PR 126P	PRXRT31	13 1/2 J	13.0-14.0	37.52	15.54	20.4	BLK
	40X15.50R26LT	10PR 126P	PRXRT23	12 1/2 J	12.5-14.5	39.52	15.43	20.4	BLK
00"	40X15.50R28LT	10PR 126P	PRXRT24	13 1/2 J	13.0-14.0	39.52	15.54	20.4	BLK
28"	42X15.50R28LT	10PR 128P	PRXRT25	131/21	12.5-14.5	41.52	15.43	20.4	BLK





^{*}Every effort has been made to verify the accuracy of the listed specifications.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





NEW MUTANT RTTRAIL

Rugged Terrain Tire



- Optimized void-to-lug ratio for extreme off-road conditions provides unparalleled traction in mud, snow, sand, and rocky terrain.
- Advanced tread pattern and pitch variation tame road noise for a smoother highway ride and increase comfort for drivers and passengers.
- Thick and stylish 3-dimensional sidewall and shoulder lugs that look good and provide puncture and impact resistance on the most rugged terrain.
- Deep, multi-functional tread grooves and siping provide enhanced traction in a wide variety of road conditions.
- An advanced all-terrain tread compound featuring increased tread life and improved on- and off-road













WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
	LT235/80R17	10PR 120/117Q	PRRT03R	6 1/2 J	6.0-8.0	31.81	9.25	17.4	RWL	
	LT235/80R17	10PR 120/117Q	PRRT03	61/2J	6.0-8.0	31.81	9.25	17.4	BLK	
	LT245/75R17	10PR 121/118Q	PRRT04	7,1	6.5-8.0	31.50	9.76	17.4	BLK	
	LT265/70R17	10PR 123/120Q	PRRT05	8.1	7.0-9.0	31.65	10.71	16.5	BLK	
	LT285/70R17	10PR 126/123Q	PRRTO6R	8 1/2 J	7.5-9.5	32.76	11.50	16.5	RWL	
17"	LT285/70R17	10PR 126/123Q	PRRT06	8 1/2 J	7.5-9.5	32.76	11.50	16.5	BLK	
"	33X12.50R17LT	10PR 120Q	PRRT07	10J	8.5-11.0	32.52	12.50	18.5	BLK	
	35X11.50R17LT	10PR 128Q	PRRT47	9,1	7.5-10.0	34.52	11.42	18.5	BLK	
	35X12.50R17LT	10PR 125R	PRRT08R	10J	8.0-10.5	34.52	12.50	18.5	RWL	
	35X12.50R17LT	10PR 125R	PRRT08	10J	8.0-10.5	34.52	12.50	18.5	BLK	
	40X13.50R17LT	8PR128Q	PRRT50	11J	9.0-11.5	39.52	13.58	18.5	BLK	
	LT275/65R18	10PR 123/120Q	PRRT09	8J	8.0-9.5	32.09	10.98	16.5	BLK	7
18"	LT275/70R18	10PR 125/122R	PRRT10	8J	7.0-9.0	33.19	10.98	16.5	BLK	
10	33X12.50R18LT	10PR 118Q	PRRT11	10J	8.5-11.0	32.52	12.50	18.5	BLK	
	35X12.50R18LT	10PR 123R	PRRT12	10J	8.5-11.0	34.52	12.50	18.5	BLK	
	275/55R20	117T XL	PRRT13	8 1/2 J	7.5-9.5	31.89	11.18	13.6	BLK	
	275/60R20	115T	PRRT15	8J	7.5-9.5	32.99	10.98	13.6	BLK	
20"	285/55R20	116T XL	PRRT17	9,1	8.0-10.0	34.09	10.98	13.6	BLK	
	305/55R20	116R	PRRT20	9 1/2 J	8.5-11.0	33.23	12.44	13.6	BLK	
	LT275/55R20	10PR 120/117S	PRRT14	8 1/2 J	8.0-9.5	31.89	11.18	16.5	BLK	EV

WHEEL DIAMETER	SIZE	L.S	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	EV READY
	LT275/60R20	10PR 123/120S	PRRT53	8J	8.0-9.5	32.99	10.98	16.5	BLK	EV
	LT275/65R20	10PR 126/123S	PRRT16	8J	8.0-9.5	34.09	10.98	16.5	BLK	EV
	LT285/55R20	10PR 122/119S	PRRT18	9,1	8.5-10.0	32.36	11.69	16.5	BLK	
	LT285/65R20	10PR 127/124S	PRRT19	8 1/2 J	8.5-10.0	34.57	11.50	16.5	BLK	EV
	LT305/55R20	12PR 125/122Q	PRRT21	91/2J	9.0-11.0	33.23	12.44	16.5	BLK	
	33X11.50R20LT	10PR 118Q	PRRT46	9,1	8.0-10.5	32.52	11.42	16.5	BLK	
	33X12.50R20LT	10PR 114Q	PRRT01	10J	8.5-11.0	32.52	12.50	18.5	BLK	
20"	33X12.50R20LT	12PR 119Q	PRRT02	10J	8.5-11.0	32.52	12.50	18.5	BLK	
	35X11.50R20LT	10PR 124Q	PRRT22	9,1	8.0-10.5	34.52	11.42	16.5	BLK	
	35X12.50R20LT	10PR 117Q	PRRT23	10J	8.5-11.0	34.52	12.50	18.5	BLK	
	35X12.50R20LT	12PR 125Q	PRRT24	10J	8.5-11.0	34.52	12.50	18.5	BLK	
	35X13.50R20LT	12PR 126Q	PRRT26	111	9.5-12.0	34.52	13.58	18.5	BLK	
	37X11.50R20LT	10PR 128Q	PRRT49	9,1	7.5-10.0	36.52	11.42	16.5	BLK	
	37X12.50R20LT	12PR 128Q	PRRT25R	10J	8.5-11.0	36.52	12.50	18.5	RWL	
	37X12.50R20LT	12PR 128Q	PRRT25	10J	8.5-11.0	36.52	12.50	18.5	BLK	
	38X15.50R20LT	10PR 128Q	PRRT27	12 1/2 J	11.0-14.0	37.52	15.54	18.5	BLK	
	HL275/50R22	116H XL	PRRT28	8 1/2 J	7.5-9.5	32.87	11.18	13.6	BLK	EV
22"	LT285/50R22	10PR 121/118Q	PRRT29	9,1	8.5-10.0	33.27	11.69	16.5	BLK	
22	LT285/55R22	10PR 124/121S	PRRT54	9,1	8.5-10.0	34.37	11.69	16.5	BLK	EV
	LT305/55R22	10PR 122/119S	PRRT55	91/2J	9.0-11.0	35.24	12.44	16.5	BLK	EV

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW	TD 32ND	SIDEWALL	RE/
	33X12.50R22LT	10PR 109Q	PRRT31	10 1/2 J	10.0-12.0	32.52	12.45	18.5	BLK	
	33X12.50R22LT	12PR 114Q	PRRT32	10 1/2 J	10.0-12.0	32.52	12.45	18.5	BLK	
	33X13.50R22LT	12PR 114Q	PRRT33	11J	10.5-12.0	32.52	13.58	18.5	BLK	
22"	33X14.50R22LT	12PR 115Q	PRRT34	13 J	12.5-14.0	32.52	15.16	18.5	BLK	
	35X12.50R22LT	10PR 117Q	PRRT35	10J	8.5-11.0	34.52	12.50	18.5	BLK	
	35X12.50R22LT	12PR 121Q	PRRT36	10J	8.5-11.0	34.52	12.50	18.5	BLK	
	35X13.50R22LT	12PR 122Q	PRRT37	111	10.5-12.0	34.52	13.58	18.5	BLK	
1	285/40R24	112H XL	PRRT38	10J	9.5-11.0	32.99	11.42	13.6	BLK	11
	LT295/45R24	10PR 120/117R	PRRT56	10J	9.5-11.0	34.49	11.65	16.5	BLK	
24"	33X13.50R24LT	12PR 113Q	PRRT39	12J	11.5-12.5	32.52	13.58	18.5	BLK	
24	33X14.50R24LT	12PR 118Q	PRRT40	13J	12.5-14.0	32.52	13.44	18.5	BLK	
	35X13.50R24LT	12PR 116Q	PRRT41	12J	11.5-13.5	34.52	13.44	18.5	BLK	
	35X14.50R24LT	10PR 118Q	PRRT42	13J	12.5-14.0	34.52	14.46	18.5	BLK	
	35X15.50R24LT	12PR 117Q	PRRT43	143	13.0-15.5	34.52	15.52	18.5	BLK	
26"	305/30R26	109H XL	PRRT44	11J	10.5-11.5	33.23	12.32	13.6	BLK	
20	LT305/35R26	10PR 108/104Q	PRRT48	11,1	10.0-12.0	34.41	12.32	16.5	BLK	

^{*}Every effort has been made to verify the accuracy of the listed specifications.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.







NEW MUTANT X-AT

All-Terrain Tire















- Advanced All-Terrain Tread Compound: This new silica tread compound delivers a perfect balance of extended tread life and improved traction on both paved and unpaved surfaces.
- Deep, Multi-Functional Grooves and Siping: These features enhance traction in a wide variety of road conditions, including wet, dry, and off-road environments
- Staggered Shoulder Lugs: The lugs offer a biting edge for superior grip on rocky terrain.
- Wider Contact Patch: This design provides increased handling stability for both on-road and off-road driving.
- Advanced "X" Tread Pattern with Pitch Variation: This design reduces road noise for a quieter highway ride, enhancing comfort for drivers and passengers.
- Aggressive "SPIKE" X-AT Dual Sidewall Design: This design not only delivers additional off-road traction and sidewall protection but also offers drivers a unique visual customization option.

WHEEL DIAMETER	SIZE	LS	PARTS Number	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD Inch	SW INCH	TD 32ND	SIDEWALL	3PMSF
15"	LT235/75R15	6PR 104/101S	NPRXATS1	61/2J	6.0-8.0	28.86	9.25	15.1	BLK	Y
	245/70R16	111T XL	NPRXATS4	73	6.5-8.0	29.53	9.76	12.1	BLK	Y
	265/70R16	112T	NPRXATS5	8.J	7.0-9.0	30.63	10.71	12.1	BLK	Y
	265/75R16	116T	NPRXATS6	71/2J	7.0-9.0	31.65	10.51	12.1	BLK	Y
16"	LT225/75R16	10PR 115/112S	NPRXATS2	6.1	6.0-7.5	29.29	8.78	15.1	BLK	Y
	LT235/85R16	10PR 120/116S	NPRXATS3	61/2J	6.0-7.5	31.73	9.25	15.1	BLK	Y
	LT265/75R16	10PR 123/120R	NPRXAT01	71/23	7.0-9.0	31.65	10.51	15.1	BLK	Y
	LT285/75R16	10PR 126/123R	NPRXAT02	8.1	7.5-9.5	32.83	11.26	15.1	BLK	Y
	245/65R17	111T XL	NPRXATS8	7,1	7.0-8.5	29.53	9.76	12.1	BLK	Y
	265/65R17	112T	NPRXATS11	8.J	7.5-9.5	30.55	10.71	12.1	BLK	Y
	265/70R17	1158	PRXAT03SF	8.1	7.0-9.0	31.65	10.71	12.1	BLK	Y
	LT235/80R17	10PR 120/117S	NPRXATS7	61/2J	6.0-8.0	31.81	9.25	15.1	BLK	Y
	LT245/70R17	10PR 119/116S	NPRXATS9	7,1	6.5-8.0	30.55	9.76	15.1	BLK	Y
17"	LT245/75R17	10PR 121/118S	NPRXATS10	7,1	6.5-8.0	31.50	9.76	15.1	BLK	Y
17	LT265/65R17	10PR 120/117S	NPRXAT05	8.J	8.0-9.5	30.55	10.71	15.1	BLK	Y
	LT265/70R17	10PR 121/118Q	PRXAT04SF	8.J	7.0-9.0	31.65	10.71	15.1	BLK	Y
	LT285/70R17	10PR 121/118Q	PRXATO6SF	8 1/2 J	7.5-9.5	32.76	11.50	15.1	BLK	Y
	33X12.50R17LT	10PR 120Q	PRXAT08SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	35X10.50R17LT	10PR 121R	PRXAT09SF	8 1/2 J	7.0-9.0	34.52	10.54	15.1	BLK	Y
	35X11.50R17LT	10PR 128Q	PRXAT68	9,1	7.5-10.0	34.52	11.42	15.1	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS Number	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW	TD 32ND	SIDEWALL	3PMSI
17"	35X12.50R17 LT	10PR 121R	PRXAT10SF	10J	8.0-10.5	34.52	12.50	15.1	BLK	γ
"	37X12.50R17LT	12PR 128Q	PRXAT66	10J	8.0-10.5	36.52	12.50	15.1	BLK	Y
13	235/60R18	107H XL	NPRXATS12	7,1	6.5-8.5	29.09	9.45	12.1	BLK	Y
	245/60R18	109H XL	NPRXATS13	7.3	7.0-8.5	29.57	9.76	12.1	BLK	y
	265/60R18	114T XL	NPRXATS14	8.1	7.5-9.5	30.51	10.71	12.1	BLK	Y
	265/65R18	116T XL	NPRXATS15	8.1	7.5-9.5	31.54	10.71	12.1	BLK	Y
18"	275/65R18	116T	NPRXATS16	8.1	7.5-9.5	32.09	10.98	12.1	BLK	Y
18	LT265/60R18	10PR 119/116R	NPRXAT11	8.1	8.0-9.5	30.51	10.71	15.1	BLK	Y
	LT265/70R18	10PR 124/121S	NPRXATS17	8J	7.0-9.0	32.64	10.71	15.1	BLK	Y
	LT275/70R18	10PR 125/122R	PRXAT12SF	8.1	7.0-9.0	33.19	10.98	15.1	BLK	Y
	LT285/65R18	10PR 125/122R	PRXAT13SF	8 1/2 J	8.5-10.0	32,56	11.50	15.1	BLK	Y
	33X12.50R18LT	10PR 118Q	PRXAT15SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	35X12.50R18 LT	10PR 123R	PRXAT16SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	265/50R20	111H XL	PRXAT67	8 1/2 J	7.5-9.5	30.47	10.91	12.1	BLK	Y
	275/55R20	117T XL	PRXAT17SF	8 1/2 J	7.5-9.5	31.89	11.18	12.1	BLK	Y
	275/60R20	115T	PRXAT19SF	8.1	7.5-9.5	32.99	10.98	12.1	BLK	Y
20"	LT275/55R20	10PR 120/117Q	PRXAT18SF	8 1/2 J	8.0-9.5	31.89	11.18	15.1	BLK	Y
	LT275/60R20	10PR 123/120R	NPRXAT20	8.1	8.0-9.5	32.99	10.98	15.1	BLK	Y
	LT275/65R20	10PR 126/123R	NPRXAT21	8J	8.0-9.5	34.09	10.98	15.1	BLK	Y
	LT285/55R20	10PR 122/119Q	PRXAT22SF	9,1	8.5-10.0	32.36	11.69	15.1	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW	TD 32ND	SIDEWALL	3PMS
11/1	LT285/60R20	10PR 125/122R	PRXAT60	8 1/2 J	8.5-10.0	33.46	11.50	15.1	BLK	Y
	LT285/65R20	10PR 127/124R	NPRXATS18	8 1/2 J	8.5-10.0	34.57	11.50	15.1	BLK	Y
	LT295/60R20	10PR 126/123S	PRXAT61	8 1/2 J	8.5-10.5	33.94	11.77	15.1	BLK	Y
	LT295/65R20	10PR 129/126P	PRXAT62	8 1/2 J	8.5-10.5	35.12	11.77	15.1	BLK	Y
	33X11.50R20LT	10PR 118Q	PRXAT23SF	9,1	8.0-10.5	32.52	11.42	15.1	BLK	Y
20"	33X12.50R20LT	10PR 114Q	PRXAT25SF	10J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	33X12.50R20LT	12PR 119Q	PRXAT26SF	10 J	8.5-11.0	32.52	12.50	15.1	BLK	Y
	35X11.50R20LT	10PR 124R	NPRXAT24	9,1	8.0-10.5	34.52	11.42	15.1	BLK	Y
	35X12.50R20LT	10PR 121Q	PRXAT27SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	35X12.50R20LT	12PR 125Q	PRXAT28SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	37X12.50R20LT	12PR 128Q	PRXAT63	10J	8.5-11.0	36.52	12.50	15.1	BLK	Y
	37X13.50R20 LT	12PR 128Q	PRXAT29SF	11,1	9.5-12.0	36.52	13.58	15.1	BLK	Y
	285/45R22	114T XL	PRXAT30SF	91/23	9.0-10.5	32.09	11.22	12.1	BLK	Y
	305/40R22	114H XL	NPRXAT31	111	10.0-12.0	31.61	12.32	12.1	BLK	Y
	LT285/55R22	10PR 124/121S	PRXAT69	9,1	8.5-10.0	34.37	11.69	15.1	BLK	Y
22"	33X12.50R22LT	10PR 109R	PRXAT32SF	10J	10.0-12.0	32.52	12.45	15.1	BLK	Y
~~	33X12.50R22LT	12PR 114Q	PRXAT33SF	10J	10.0-12.0	32.52	12.45	15.1	BLK	Y
	35X12.50R22LT	10PR 117R	PRXAT34SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	35X12.50R22LT	12PR 121Q	PRXAT35SF	10J	8.5-11.0	34.52	12.50	15.1	BLK	Y
	37X13.50R22 LT	12PR 128Q	PRXAT36SF	111	9.5-12.0	36.52	13.58	15.1	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS Number	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL	3PMSF
	33X12.50R24 LT	12PR 106Q	PRXAT64	11 1/2 J	10.5-12.5	32.52	12.60	15.1	BLK	Y
	33X13.50R24 LT	12PR 113Q	PRXAT37SF	12 1/2 J	11.5-12.5	32.52	13.58	15.1	BLK	Y
24"	35X12.50R24LT	12PR 116Q	PRXAT65SF	10 1/2 J	10.0-12.0	34.52	12.45	15.1	BLK	Y
	35X13.50R24LT	12PR 116Q	PRXAT38SF	12 J	11.5 - 13.5	34.52	13.44	15.1	BLK	Y
	37X13.50R24LT	12PR 124Q	PRXAT39SF	11,1	9.5-12.0	36.52	13.58	15.1	BLK	Y
- 77	35X12.50R26LT	12PR 115Q	PRXAT42SF	11 1/2 J	11.0-12.0	34.52	12.45	15.1	BLK	Y
26"	37X12.50R26LT	12PR 117Q	PRXAT43SF	10 J	9.5-11.5	36.52	12.50	15.1	BLK	Y
	37X13.50R26LT	12PR 117Q	PRXAT40SF	11,1	10.5-13.0	36.52	13.44	15.1	BLK	Y



^{*}Every effort has been made to verify the accuracy of the listed specifications.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

Brave the winter with confidence with the New Mutant Arctic. which is a studdable winter tire designed specifically for light trucks and SUVs. It delivers confidence-inspiring performance in harsh winter conditions. The New Mutant Arctic features a directional tread design, a winter-optimized tread compound, and industry-leading construction techniques. This combination ensures excellent traction, improved braking, and superior hydroplaning resistance, even in severe winter weather. 27 NEW MUTANT ARCTIC

NEW MUTANT ARCTIC



Light Truck Winter Tire



^{*}Ratings are on a scale of 1-10

- Increased sipe density and interlocking ripple design create more biting edges for controlled handling on ice

Superior winter tread compound delivers improved

Wide circumferential grooves channel snow and evacuate water and slush for enhanced hydroplaning

traction and balanced handling in winter conditions.

- Large, squared-off shoulder blocks provide a wider contact patch for greater stability and handling.
- Studdable with seven rows of pin holes across the contact patch for the ultimate traction on ice and compacted snow.

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD Inch	SW INCH	TD 32ND	SIDEWALL	3PMS
	235/65R16C	10PR 121/119R	PNMICE01	7,1	6.5-7.5	28.03	9.45	16.0	BLK	Y
16"	LT225/75R16	10PR 115/112Q	PNMICE02	6.3	6.0-7.5	29.29	8.78	16.0	BLK	Y
	LT245/75R16	10PR 120/116R	PNMICE03	7,1	6.5-8.0	30.47	9.76	16.0	BLK	Y
	265/70R17	116T XL	PNMICE21	81	7.0-9.0	31.65	10.71	12.6	BLK	Y
	LT245/75R17	10PR 121/118Q	PNMICE05	7,1	6.5-8.0	31.5	9.76	16.0	BLK	Y
17"	LT265/70R17	10PR 123/120Q	PNMICE06	8J	7.0-9.0	31.65	10.71	16.0	BLK	Y
	LT285/70R17	10PR 126/123Q	PNMICE04	8 1/2 J	7.5-9.5	32.76	11.50	16.0	BLK	Y
	33X12.50R17LT	10PR 120R	PNMICE14	10J	8.5-11.0	32.52	12.50	16.0	BLK	Y
	35X12.50R17LT	10PR 125R	PNMICE15	10J	8.0-10.5	34.52	12.50	16.0	BLK	γ
	37X12.50R17LT	10PR 128Q	PNMICE25	10J	8.0-10.5	36.52	12.50	16.0	BLK	Y
	275/65R18	116T XL	PNMICE22	8J	7.5-9.5	32.09	10.98	12.6	BLK	γ
	LT275/65R18	10PR 123/120R	PNMICE08	8J	8.0-9.5	32.09	10.98	16.0	BLK	Y
	LT275/70R18	10PR 125/122R	PNMICE07	8J	7.0-9.0	33.19	10.98	16.0	BLK	Y
18"	LT285/65R18	10PR 125/122R	PNMICE20	8 1/2 J	8.5-10.0	32.56	11.50	12.6	BLK	Y
	33X12.50R18LT	10PR 118R	PNMICE16	10J	8.5-11.0	32.52	12.50	16.0	BLK	Y
	35X12.50R18LT	10PR 123R	PNMICE17	10J	8.5-11.0	34.52	12.50	16.0	BLK	Y
	37X12.50R18LT	12PR 128Q	PNMICE26	10J	8.0-10.5	36.52	12.50	16.0	BLK	Y
	275/55R20	117T XL	PNMICE23	81/21	7.5-9.5	31.89	11.18	12.6	BLK	γ
20"	275/60R20	115T	PNMICE10	8.J	7.5-9.5	32.99	10.98	12.6	BLK	Y
	LT275/65R20	10PR 126/123R	PNMICE11	8.J	8.0-9.5	34.09	10.98	16.0	BLK	Y

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW	TD 32ND	SIDEWALL 3PMS	
20"	33X12.50R20LT	10PR 114R	PNMICE12	10J	8.5-11.0	32.52	12.50	16.0	BLK	Y
20	35X12.50R20LT	10PR 121R	PNMICE13	10J	8.5-11.0	34.52	12.50	16.0	BLK	Y
13	275/50R22	115T XL	PNMICE24	8 1/2 J	7.5-9.5	32.87	11.18	12.6	BLK	Y
22"	285/45R22	114T XL	PNMICE09	91/21	9.0-10.5	32.09	11.22	12.6	BLK	~ Y
22	33X12.50R22LT	10PR 109R	PNMICE18	101/23	10.0-12.0	32.52	12.45	16.0	BLK .	Y
	35X12.50R22LT	10PR 117R	PNMICE19	10J	8.5-11.0	34.52	12.50	16.0	BLK	- 4-





^{*}Every effort has been made to verify the accuracy of the listed specifications.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

Built for discerning drivers, the all-new Predator Comptrax PR1 A/S ultra high performance tire seamlessly blends cutting-edge design with uncompromising performance for crisp handling and comfort across all seasons.

Featuring a striking aesthetic, advanced tread design, and innovative tire compound, the Comptrax PR1 A/S delivers confident control. elevating your driving experience in a way that embodies our brand's relentless pursuit of performance. The Comptrax PR1 A/S carves through corners with precision, while maintaining a luxuriously quiet ride. Backed by a 40,000-mile warranty and a full year of road hazard protection, this all-season performer offers miles of confidence and sculpted style for your car, crossover, truck, or SUV.

Comptrax PRI A/S

All-Season Ultra High Performance

555	Dry Performance	
		9.0
A	Wet Performance	
		8.0
*	Winter Performance	
4.		5.0
\approx	Ride Comfort	
*		8.0
M)	Quiet Ride	
1	*Ratings are on a scale of 1-10	9.0

- Deep sipes along the inner shoulder tread blocks and central tread blocks improve water evacuation on wet roads and interlock during cornering, providing enhanced dry traction and improved braking performance.
- A solid circumferential rib positioned next to the outer shoulder blocks enhances responsive handling and increases straight-line
- Ranging from 16-inch to 24-inch applications, the Predator Comptrax PR1 A/S is available in 37 sizes with more on the way.











WHEEL DIAMETER	SIZE	LS	PARTS Number	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD Inch	SW	TD 32ND	SIDEWALL
16"	205/55ZR16	91W	PDCPAS01	61/2J	5.5 - 7.5	24.88	8.43	10.0	BLK
~	215/45ZR17	91W XL	PDCPAS03	71	7.0 - 8.0	24.65	8.39	10.0	BLK
17"	215/55R17	940	PDCPAS05	7,1	6.0 - 7.5	26.30	8.90	10.0	BLK
II .	225/50ZR17	98W XL	PDCPAS07	7,1	6.0 - 8.0	25.91	9.17	10.0	BLK
	225/55R17	101V XL	PDCPASO8	71	6.0 - 8.0	26.77	9.17	10.0	BLK
	235/45R18	98V XL	PDCPAS14	8J	7.5 - 9.0	26.34	9.29	10.0	BLK
"	235/50ZR18	101W XL	PDCPAS15	71/2J	6.5 - 8.5	27.28	9.65	10.0	BLK
18"	235/55R18	104V XL	PDCPAS16	71/2J	6.5 - 8.5	28.15	9.65	10.0	BLK
	245/45ZR18	100W XL	PDCPAS18	8.J	7.5 - 9.0	26.65	9.57	10.0	BLK
10"	235/40ZR19	96W XL	PDCPAS21	8 1/2 J	8.0 - 9.5	26.42	9.49	10.0	BLK
19"	245/40ZR19	98W XL	PDCPAS24	8 1/2 J	8.0 - 9.5	26.73	9.76	10.0	BLK
	245/35ZR20	95W XL	PDCPAS26	8 1/2 J	8.0 - 9.5	26.77	9.76	10.0	BLK
00"	245/40ZR20	99W XL	PDCPAS27	8 1/2 J	8.0 - 9.5	27.72	9.76	10.0	BLK
20"	245/45ZR20	103W XL	PDCPAS28	8,1	7.5 - 9.0	28.66	9.57	10.0	BLK
	275/40ZR20	106W XL	PDCPAS29	91/2J	9.0 - 11.0	28.66	10.94	10.0	BLK
20"	265/35ZR22	102W XL	PDCPAS31	91/2J	9.0 - 10.5	29.33	10.67	10.0	BLK
22"	305/40R22	114V XL	PDCPAS33	UI)	10.0 - 12.0	31.61	12.32	10.0	BLK
24"	305/35R24	112V XL	PDCPAS37	11,1	10.0 - 12.0	32.44	12.32	10.0	BLK

^{*}Every effort has been made to verify the accuracy of the listed specifications.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.





Three main grooves work together with curved lateral channels to efficiently evacuate water, helping maintain contact with the road in wet weather.



STEEL PAYLOAD

Predator All Steel ST



 Advanced all-steel belt construction for improved durability and increased payload.

 Patented polymer tread compound lowers rolling resistance, helping improve fuel economy and tread life.

Four circumferential grooves channel and disperse water and slushy snow to prevent hydroplaning.

- Symmetrical ribbed tread design delivers directional stability. driving smoothness and low rolling resistance.
- Enhanced sidewall ribs to prevent curbing damage on the tire
- Improved tread profile for a wider tire stance for better weight distribution, promoting even tire wear and increased tread life.

The Predator All Steel ST is a durable all-steel radial construction highway trailer tire for heavy-duty hauling applications. The combination of a newly formulated tread compound and advanced tire carcass design achieves low rolling resistance and extended service life, making fleets maximize fuel efficiency and lower total cost of

WHEEL DIAMETER	SIZE	LS	PARTS NUMBER	STANDARD RIM	APPROVED RIM WIDTH RANGE	OD INCH	SW INCH	TD 32ND	SIDEWALL
_1) [[.]	ST205/90R15	G/14PR 125/120L	PTST02	5 1/2 J	5.0-6.5	29.53	7.99	9.57	BLK
15"	ST225/75R15	F/12PR 121/117M	PTST03	6.3	6.0-7.5	28.31	8.78	10.2	BLK
	ST225/75R15	G/14PR 123/119L	PTST04	6.1	6.0-7.5	28.31	8.78	10.2	BLK
	ST235/80R16	G/14PR 129/125M	PTST05	61/2J	6.0-8.0	30.79	9.25	9.57	BLK
16"	ST235/80R16	H/16PR 130/126L	PTST06	61/2J	6.0-8.0	30.79	9.25	9.57	BLK
	ST235/85R16	G/14PR 132/127M	PTST07	61/2J	6.0-7.5	31.73	9.25	11.46	BLK
	ST235/85R16	H/16PR 133/128L	PTST08	61/2J	6.0-7.5	31.73	9.25	11.46	BLK

^{*}Every effort has been made to verify the accuracy of the listed specifications.

Transamerica Tire cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.



PREDATOR TIRE

LIMITED WARRANTY

STANDARD COVERAGE

If your PREDATOR TIRES becomes unserviceable as a result of an eligible adjustable condition during the first 10% of tread life, the owner will be compensated 100% of the value of the tire. After that amount, PREDATOR TIRES will offer a prorated mileage credit, down to 25% remaining tread depth, towards purchasing a comparable PREDATOR brand tire. The owner must pay for mounting, balancing, and any other additional charges, such as taxes and freight, PREDATOR TIRES shall not be responsible for any other fees incurred as a part of any exchange, labor, or additional costs resulting from this guarantee, PREDATOR TIRES shall not be responsible for any damage or other issues caused by the improper installation (including any of the exclusions below), balancing, or selection of tire—including the selection of size, specification, type, or use of such tire (including those obligations under the "Owner's Obligations section below") that the manufacturer of your vehicle does not recommend. All terms and conditions of this guarantee are limited to the terms and conditions contained in this guarantee.

PREDATOR TIRES include the Standard Coverage and the additional coverages listed below.

MILEAGE WARRANTY

- 50,000 miles tread life warranty for New Mutant X-AT and New Mutant X-RT 22-inch and smaller, and 13.5-inch wide or less.
- 50,000 miles tread life warranty for Comptrax PR1 A/S.
- 55,000 miles tread life warranty for New Mutant RT TRAIL 22-inch and smaller, and 13,5-inch wide or less.
- Vehicles with staggered fitments, where the front and rear tires have different tire sizes, cannot be rotated. PREDATOR TIRES warrants tires mounted on the rear axle of vehicles with staggered fitments only up to 50% of the warranted miles under our standard mileage warranty for specific tire models, tread patterns, and tire sizes.

PREDATOR TIRES are warrantied against treadwear prior to the applicable indicated mileage for each specific tire model and size, provided that you:

- 1. Rotate your tires following the prescribed rotation patterns at least every 3,500 miles or less (UHP passenger car tires) or 5,000 miles or less (standard light truck tires) and have documentation showing the rotation schedule.
- 2. The TIRE SERVICE RECORD form filled out by the tire shop, dealer, or service department during regular routine maintenance. The required TIRE SERVICE RECORD form can be downloaded at the bottom of this page. In lieu

of the TIRE SERVICE RECORD form given to you by a PREDATOR TIRES dealer, you may use acceptable service records from an oil change shop or car dealer service department that the recommended tire rotation has been performed.

- Present the subject tire for adjustment during regular routine maintenance.
- 4. Present documentation showing the rotation schedule when requesting an adjustment and the date of purchase, vehicle type, model, odometer reading, and tire pressure

When the tread becomes worn to 2/32 inch (shown by tread wear indicators molded into the tread grooves), the tire tread shall be considered worn. The Department of Transportation specifications determine such tread wear. and in accordance with applicable laws and regulations.

4-YEAR MANUFACTURER WARRANTY

The 4-Year Manufacturer Warranty is a non-prorated replacement for any manufacturing defects in material and workmanship under normal and intended use. Non-intended uses include racing, off-road use, or competition use. If a manufacturing defect in material or workmanship occurs, the tire will be replaced at no charge, on a non-prorated basis to the consumer.

CONDITIONS AND EXCLUSIONS

PREDATOR TIRES warranties are limited to the original purchaser and the original vehicle on which they are installed, and such warranties and quarantees are not assignable to subsequent purchasers or vehicles. All warranties and guarantees by PREDATOR TIRES are only applicable in the United States and Canada. This warranty does not cover any tires used or equipped on a vehicle registered or operated outside the United States and Canada.

The Limited Warranty does NOT cover the following:

- Tire branded or marked "blem," "Non-Adjustable (N/A)," or previously adjusted.
- · Failure, damage, or irregular wear due to:
- Road hazards (i.e., punctures, cuts, snags, bruises, impact breaks, etc.), wreck or collision;
- . Fire accident or vandalism:
- Mechanical condition of the vehicle, including misalignment, wheel imbalance, faulty shocks or brakes:
- Misapplication of tire or use of improper inner tube;
- . Alteration of the tire or addition of foreign material.
- . Use of tire chains, tire spinning, racing, off-road use, or other competitive activities.

- Non-factory vehicle staggered tire fitments.
- Costs of mounting and balancing service.
- . Costs related to tire pressure monitoring systems.
- . Costs related to shipping and transportation of the tire.

Loss of time or use, inconvenience, or any incidental or consequential damages.

- Improper use or operation including, but not limited to: improper tire and vehicle maintenance, running flat or run with severe underinflation, misuse, abuse, accident fire or chemical corrosion, underinflation, overinflation, overloading, over deflection, or failure to follow recommended rotation practices.
- Improper installation, improper mounting or dismounting, misapplication, improper repairs, wheel misalignment, or imbalance in the tire/wheel assembly.
- Tire size, load, and speed rating do not match the tire specifications outlined in your vehicle owner's manual.
- Tires with the Department of Transportation (DOT) number removed or rendered illegible; tires must bear the DOT prescribed tire identification numbers.
- Ride complaints after the first 1/32nd of tread wear or due to damaged wheels or any vehicle condition.

PREDATOR TIRES do not warrant any work performed by the dealer including, but not limited to their selection, fitment, mounting and balancing, inspection, or repair of any tire.

INELIGIBLE TIRES

Tires are not eligible for warranty if:

- The mileage and tire rotation records are not available or verifiable.
- The subject tire or tires are not presented and available for inspection at an authorized dealer.

- The subject tire or tires are worn beyond the tread wear bar indicators (less than 2/32nd of remaining tread).
- . Uniformity issues after the first 1/32nd of tread wear.

CONSUMER RIGHTS

This Limited Warranty gives you specific legal rights; you may also have other rights, which vary from state to state.

PREDATOR TIRES disclaims all other warranties, express or implied, including the implied warranty of merchantability, the implied warranty of fitness for a particular purpose and liability for incidental and consequential damages (i.e., loss of time, loss of use of vehicle, road services, towing charges, inconveniences, etc.).

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions may not apply to you.

NO ONE (including a PREDATOR TIRES employee, representative, or dealer) has the authority to vary the terms of this Limited Warranty.*

OWNER'S OBLIGATION

When making a claim, you must return the tire to be replaced to your PREDATOR TIRES dealer and sign the customer signature section of the PREDATOR TIRES Claim Form.

Proper vehicle and tire care are necessary to obtain the expected wear from a tire. Therefore, it is your obligation to properly maintain your tires and the vehicle upon which they are mounted, including:

- 1. Operating your tires at the inflation pressures recommended by the tire and vehicle manufacturer.
- 2. Keeping your tire and wheel assemblies in balance.
- 3. Proper wheel alignment.
- 4. Maintaining steering and suspension components to be within manufacturer specifications.
- 5. Rotating your tires at least every 5,000 miles or less (standard light truck tires).

We recommend that you have your PREDATOR TIRES dealer inspect your tires any time you notice irregular or uneven tread wear and rotate them, if necessary,

Failure to follow any of the above-mentioned Owner Obligations may be considered a breach of the warranty agreement and result in the termination of the warranty agreement. Furthermore, PREDATOR TIRES reserves the right to review each warranty claim and deny the warranty application based on failing to follow any of the above-mentioned Owner Obligations.

* PREDATOR TIRES reserves the right to change the terms and conditions of all warranties at any time.

CLAIMS PROCESS

To make a claim under this Limited Warranty, you must

- 1. Present your vehicle with the subject tires, the original copy of this Limited Warranty, and the original sales invoice to an authorized PREDATOR TIRES dealer.
- 2. Present your completed Tire Service Record to the authorized PREDATOR TIRE dealer along with the other two documents in #1. For treadwear mileage warranty consideration, the Tire Service Record must show the times and places that the tire rotations were performed, PREDATOR TIRES recommends rotations at 5,000-mile intervals or less for standard light truck tires,
- 3. Complete and sign the PREDATOR TIRES Limited Warranty Claim form provided by the dealer, keep a copy for your records, and leave the tire with the dealer.
- 4. If you purchased the tire from an Internet or mail-order merchant, you will need to submit your claim, together with the dismounted tire, to that merchant. You are responsible for all of the costs of dismounting and shipping. Your claim will be administered in accordance with the Limited Warranty that was in effect when you purchased the tires.

37 PREDATOR



@PREDATORTIRES

FOLLOW US

•

0

J.

WWW.PREDATORTIRES.COM
@PREDATORTIRES
marketing@transamericatire.com

TRANSAMERICA TIRE CO.,LTD.
5118 PARK AVE., SUITE 601, MEMPHIS, TN 38117
832-891-2821